



Ref N°	Wire Ø Câble Ø mm	Thread Filetage UNF	D mm	Z mm	X mm	L0min/max mm	L1min/max. mm	Break. load Charge Rupture [kg]
1312030060	3	1/4"	6.4	18.5	7.5	155-218	193.5-256.5	1200
1312040080	4	5/16"	7.9	28.5	9.0	191-262	235-306	1710
1312050080	5	5/16"	7.9	28.5	9.0	193-270	244.5-321.5	2290
1312050100	5	3/8"	9.5	33.5	11.0	218-298	270.5-350.5	2660
1312060110	6	7/16"	11.0	34.0	13.0	252-343	312-403	4500
1312060130	6	1/2"	12.7	39.0	14.0	277-366	337-426	4100
1312070130	7	1/2"	12.7	34.0	13.0	250-353	320.5-423.5	4750
1312080130	8	1/2"	12.7	39.0	14.0	274-384	350-460	5910
1312080160	8	5/8"	15.9	47.9	17.5	341-461	419-539	8450
1312100160	10	5/8"	15.9	47.9	17.5	335-478	429-572	9275
1312100190	10	3/4"	19.1	53.5	21.5	403-548	498-643	9275
1312120190	12	3/4"	19.0	53.5	21.5	399-561	531-693	10810
1312127190	12.7	3/4"	19.0	53.5	21.5	400-570	520-690	12880
1312127220	12.7	3/4"	22.2	69.9	24.0	416-592	536-712	13100
1312140220	14	7/8"	22.2	67.5	24.0	474-668	630-824	16430
1312160250	16	1"	25.0	63.0	28.0	529-769	705-945	16986