



Ref N°	Wire Ø Ø Câble mm	Pin Ø Ø Axe mm	A mm	L mm	L1 mm	C mm	Breaking load Charge Rupture [kg]
1100030070	3.0	6.4	5	17	57.0	14.5	1240
1100040090	4.0	8.1	7	19	64.0	15.7	1510
1100050100	5.0	9.6	7.5	24.5	76.0	18.4	2345
1100050110	5.0	10.5	7.5	24.5	76.0	18.7	2345
1100060110	6.0	11.2	10	29	89.0	24,4	5040
1100060130	6.0	12.8	10	25	89.0	24,4	5040
1100070130	7.0	12.8	10	30	103.0	25.0	6435
1100080130	8.0	12.8	11.5	31	110.0	29.4	8073
1100080160	8.0	16	13.5	35.5	110.0	32,8	7650
1100100160	10.0	16	13,9	39.3	136.0	32.7	8570
1100100190	10.0	19.1	16,1	42.5	136	36,3	8570
1100120190	12.0	19.2	17.5	65	180.0	36.8	10345
110012022B	12.0	22.3	19.1	66.5	180.0	45.4	10345
1100127190	12.7	19.1	18	53	180.0	38.0	11405
1100127220	12.7	22.3	21.1	65	180.0	44.0	11405
1100140220	14.0	22.3	21.3	52.5	205.0	51.0	16550
1100140250	14.0	25.6	21	61.4	196.0	51.0	15630
1100160260	16.0	25.5	23.6	88	236.0	54.5	20172
1100190290	19.0	28.7	27.2	67	275.0	62.1	23290
1100220330	22.0	32.2	30.0	70	320.0	72.2	42990